## **Product Selector**

			Product Selector			
			Dalmatian OPCORE	OPCORE)G	OPCORE	
			<b>Recycling</b> you can see.™	<b>High R-value</b> Graphite EPS	High Quality White EPS	
Protective Packaging Applications Thermal Insulation Applications	Fabricated	Impact & Crush Resistant Components				
		Thermal + Impact & Crush Resistant Components			$\bigcirc \bigcirc \bigcirc \bigcirc$	
	Box Inserts	Impact & Crush Resistant	$\bigcirc \bigcirc $		$\bigcirc \bigcirc \bigcirc$	
		Keep-Warm & Keep-Cold	$\bigcirc \bigcirc $	00000	$\bigcirc \bigcirc \bigcirc \bigcirc$	
	Stock	Block & Brace	$\bigcirc \bigcirc $			
	Insulation Boards	ASTM-C578 Compliant Foam Insulation		00000	00000	
		Max R-value per inch of thickness	000	00000	000	
		XPS Replacement		00000		
	Building Products	Fabricated Insulation for Your System				
	Window & Door	Window Profile & Hollow Door Insulation		$\bigcirc \bigcirc $	$\bigcirc \bigcirc \bigcirc$	
	Siding	Siding Insulation		00000	$\bigcirc \bigcirc \bigcirc \bigcirc$	
	Laminates	Structural Insulated Panel Cores		$\bigcirc \bigcirc $	$\bigcirc \bigcirc $	
		Multi-Layer Laminates		$\bigcirc \bigcirc $	$\bigcirc \bigcirc $	
Product Options	Properties	Density	0.9 pcf - 2.0 pcf	0.9 pcf - 3.0 pcf (lbs per cubic foot)		
		Maximum Size	48"w x 36"t x 192"l	48"w x 36"t x 192" or 216"l		
		Minimum tolerance for thickness, width, length	+/- 1/8"	+/- 1/16"		
		Shape	Rectangular & Square	Rectangular, Square, Other Polygon	s + Profiles + Cut-outs + Build-	
ustainability	Recycle	Recyclability		100% recyclable as type 6 plastic.		
	Climate	Ozone Protection	Zero CFC	Zero CFC. Zero HCFC. Zero ozone depletion potential.		
	Avoid Landfill	Recycle Material Source	Post-consumer & post-industrial.			

## Contact OPCO

800.229.6726 www.opcodirect.com