



Product Selector



Recycling
you can see.™

High R-value
Graphite EPS

High Quality
White EPS

Protective Packaging Applications

Fabricated	Impact & Crush Resistant Components			★★★★★
	Thermal + Impact & Crush Resistant Components		★★★★★	★★★
Box Inserts	Impact & Crush Resistant	★★★★★		★★★
	Keep-Warm & Keep-Cold	★★★★★	★★★★★	★★★
Stock	Block & Brace	★★★★★		

Thermal Insulation Applications

Insulation Boards	ASTM-C578 Compliant Foam Insulation		★★★★★	★★★★★
	Max R-value per inch of thickness	★★★	★★★★★	★★★
	XPS Replacement		★★★★★	
Building Products	Fabricated Insulation for Your System		★★★★★	★★★
Window & Door	Window Profile & Hollow Door Insulation		★★★★★	★★★
Siding	Siding Insulation		★★★★★	★★★
Laminates	Structural Insulated Panel Cores		★★★★★	★★★★★
	Multi-Layer Laminates		★★★★★	★★★★★

Product Options

Properties	Density	0.9 pcf - 2.0 pcf	0.9 pcf - 3.0 pcf (lbs per cubic foot)	
	Maximum Size	48"w x 36"t x 192"l	48"w x 36"t x 192" or 216"l	
	Minimum tolerance for thickness, width, length	+/- 1/8"	+/- 1/16"	
	Shape	Rectangular & Square	Rectangular, Square, Other Polygons + Profiles + Cut-outs + Build-Ups	

Sustainability

Recycle	Recyclability	100% recyclable as type 6 plastic.		
Climate	Ozone Protection	Zero CFC. Zero HCFC. Zero ozone depletion potential.		
Avoid Landfill	Recycle Material Source	Post-consumer & post-industrial.		

The information contained herein is subject to change and is provided for informational purposes only is provided without warranty, either express or implied. Opco, Inc. reserves the right to amend the information in this publication without notice.

Opco, Inc. assume no liability for any errors or omissions in the content of this publication.

OPCORE is a registered trademark of Opco, Inc. The OPCO logo is a registered trademark of Opco, Inc. Dalmatian OPCORE is a trademark of Opco, Inc. Recycling you can see is a trademark of Opco, Inc. All Rights Reserved.

Any use of this publication, including reproduction, modification, distribution or republication without prior written consent is strictly prohibited.

OPCO Rigid Foam Product Selector.pdf

Contact OPCO

800.229.6726

www.opcodirect.com